

PAINTEX 4

ACRYLIC WHITE CRACK FILLING COMPOUND

DESCRIPTION

PAINTEX-4, India's first acrylic crack filling compound, is a professional quality product. Paintex-4 prevents air and moisture from passing through cracks and joints, offers excellent flexibility to resist expansion and contraction without cracking. Paintable with latex and oil based paints. Useful for both interior as well as exterior.

CHARACTERISTICS

- Color : white and light grey
- Consistency : smooth and creamy
- Odour : Very mild
- Vehicle : Acrylic polymer
- Volatile : water
- Tooling time : 10 minutes
- Track free time : 30 minutes
- Temperature service range : -20⁰ C to 90⁰ C
- Temperature application range : 3⁰ C to 40⁰ C
- Freeze thaw stability : passes 5 cycles
- Paintability : yes
- Shelf life : 24 Months
- Max Gap filling capacity : up to 12 mm

APPLICATION

- Window and door
- Frames corner
- Joints baseboard
- Moulding
- Vents
- Sliding and trim
- Other gaps & openings

EXCELLENT ADHESION ON

- Concrete
- Plaster
- Brick
- Drywall

PAINTEX 4

ACRYLIC WHITE CRACK FILLING COMPOUND

- Painted surface
- Wood
- Metal

SURFACE PREPARATION AND APPLICATION

- Remove old caulk from surface
- Make sure that surface is clean, dry and free of loose debris
- Trim the nozzle to the desired bead size
- Then puncture the foil using any pointed object
- Load the cartridge into caulking gun
- Hold the cartridge at a 45° angle and fill the seam with ample amount of sealant

PACKING

Standard packing : 350 gm. cartridge and 1 kg tin
Color : white or light grey after drying

COVERAGE

The amount of Paintex-4 required to seal the crack can be very easily estimated by using the following formula:-

$$i) L = \frac{617}{(W \times D)}$$

Where, L = Length of the joint in linear running meter
W= Width of the joint in mm.
D = Depth of the joint in mm.

PRECAUTION

Do not use in high abrasion area or underwater

SHELF LIFE

24 Months