

SALT GUARD

ANTI EFFLORESCENCE PRIME COAT

DESCRIPTION

SALT GUARD is a specially pigmented coating which acts as an anti-efflorescence primer and prevents the growth of salt formation on the wall.

FEATURES

- Excellent alkali & efflorescence resistances
- Physical barrier to water transport
- Chemical barrier to salt migration
- Excellent substrate penetration & top-coat adhesion

BENEFITS

- Long-life high-class appearance of topcoat
- Less topcoat & re-painting required
- Ideal for high-alkaline concrete
- Prevention of top coat defects

TYPICAL APPLICATION

To be applied over concrete, plastered or brick, masonry surfaces.

TYPICAL CHARACTERISTICS

Nature	: single component, liquid
Color	: Turbid white
Specific gravity at 30 °C	: 1.08 ± 0.04
Inter-coat interval	: 4 to 6 Hrs
Dilution	: 50% potable water
Coverage	: 55-60 sq. ft. per 2 coats/ ltr.
DFT	: 30 40μ

DIRECTIONS FOR USE

FOR BRICKS & PLASTER SURFACE

Clean the surface with brush and ensure no loose particle remains on the substrate. On the clean and dry substrate apply the material with the help of a brush. Application is to be done on concrete, plastered or brick; masonry surfaces till saturation level is achieved. Allow it to dry for 1-2 Hrs. then apply second coat and after 24 hrs as top coating.

SALT GUARD

ANTI EFFLORESCENCE PRIME COAT

CLEANING OF TOOLS AND EQUIPMENT

Tools and equipment can be easily cleaned with water. If dries, it should be scrapped off.

STORAGE AND SHELF LIFE

- In order to preserve all the properties, store the material in the original un-opened containers in cool and dry place.
- Shelf life is 24 months.

PACKING

1 liter, 4 liters and 20 liters.