



DESCRIPTION

FIX TILE PEARL High polymer modified cement base tile adhesive for installing CERAMIC TILES & VITRIFIED TILES, TILE ON TILE applications for Internal areas.

RECOMMENDED USES

FIX TILE PEARL is used for the permanent fixing of ceramic, mosaic, terrazzo and cement tiles over masonry wall & floors, TILE ON TILE application.

ADVANTAGES

- It has excellent water and Impact resistance
- Excellent adhesive strength
- Good slip resistance
- Minimum shrinkage
- Highly polymer modified.
- Best workability

APPLICATION METHOD

FIX TILE PEARL should be applied after proper surface preparation. Apply using a flat trowel at a thickness of 3 mm and level it by notched trowel. The thickness of the ribs will depend upon the size of tile. Do not spread more than 1 sq. meter at a time. Fix the tiles immediately with sliding motion to avoid poor bond. Adjust the position of tile before the open time of mortar otherwise it will affect on bond strength. After the completion of fixing tiles remove the excess mortar by using a damp cloth before setting of material.

SPECIAL NOTES

Tiling in newly constructed building should not commence until all shrinkage movement and creeping has taken place. Always keep at least 2 mm of gap between two tiles. Direct sunlight, wind or rain should be avoided while application time.

Grouting should be carried out for at least 48 hours after completion of tiling.



MIXING

FIX TILE PEARL is supplied in 20 kg bags. It should be mixed with a 4.5 - 5 liter of potable clean water. Use electric agitator to achieve uniform and homogeneous mix.

PACKING

It is available in 20 kg. bag.

COLOUR

Grey

COVERAGE

Approx. 60 -65 sq.ft per bag of 20 kg with square notch trowel of 3mm bedding. The coverage depends on the conditions of the substrate and the type of tiles.

CLEANING

Water is all that needed to remove uncured mortars.

HEALTH AND SAFETY

Non hazardous. If ingested seek medical advice immediately.

TECHNICAL SERVICE

CHOKSEY CHEMICALS technical service department is pleased to offer full Technical support on specific application