


FIX TILE PREMIUM W07

TILE ADHESIVE



DESCRIPTION

FIX TILE PREMIUM W07 Multipurpose highly polymer modified cement based tile adhesive which imparts high strength, flexibility & non slip properties on vertical surface for fixing GLASS MOSAICS for internal & external areas for both floors and walls.

RECOMMENDED USES

FIX TILE PREMIUM W07 is used for the permanent fixing of GLASS MOSAICS & CLADDING TILES. Specially formulated to impart non-slip properties on vertical surfaces.

ADVANTAGES

- It has excellent water and Impact resistance
- Excellent adhesive strength
- Good slip resistance
- Minimum shrinkage
- Highly polymer modified.
- Best workability

APPLICATION METHOD

FIX TILE PREMIUM W07 should be applied after proper surface preparation. Apply using a flat trowel at a thickness of 3 mm and level it by notched trowel. The thickness of the ribs will depend upon the size of tile. Do not spread more than 1 sq. meter at a time. Fix the tiles immediately with sliding motion to avoid poor bond. Adjust the position of tile before the open time of mortar otherwise it will affect on bond strength. After the completion of fixing tiles remove the excess mortar by using a damp cloth before setting of material.


SPECIAL NOTES

Tiling in newly constructed building should not commence until all shrinkage movement and creeping has taken place. Always keep at least 2 mm of gap between two tiles. Direct sunlight, wind or rain should be avoided while application time.

Grouting should be carried out for at least 48 hours after completion of tiling.

FIX TILE PREMIUM W07

TILE ADHESIVE



MIXING

FIX TILE PREMIUM W07 is supplied in 20 kg bags. It should be mixed with a 4.5 - 5 liter of potable clean water. Use electric agitator to achieve uniform and homogeneous mix.

PACKING:

It is available in 20 kg bags.

COLOUR:

White

COVERAGE:

Approx. 60 -65 sq.ft per bag of 20 kg with square notch trowel of 3mm bedding. The coverage depends on the conditions of the substrate and the type of tiles.

CLEANING:

Water is all that needed to remove uncured mortars.

HEALTH AND SAFETY:


Non hazardous. If ingested seek medical advice immediately.

TECHNICAL SERVICE

CHOKSEY CHEMICALS technical service department is pleased to offer full Technical support on specific application.

□ FIX TILE PREMIUM W07

TILE ADHESIVE



DISCLAIMER

The data is provided in the belief that is accurate within generally accepted standards and is provided for the information of qualified personnel. There is no guarantee is assumed on the performance of work completion executed with use of our product. The users therefore should make their own determination in using the product of the data contained herein for any application.