


□ SPECTRUM TILE MATE CG 01

CEMENTITIOUS TILE GROUT



DESCRIPTION

SPECTRUM TILE MATE CG 01 is a Fine polymer modified cement based powder grout with color fast pigments to provide strong, hard, Durable, non-shrinking tile joint for grouting **GLAZED WALL TILES, MOSAICS, VITRIFIED TILES**. It is designed for joint width from 2mm to 6mm. For wider joint from 6mm to 12mm use our POLYMER LIQUID ADMIX URP to enhance adhesion, water permeability and flexibility.

RECOMMENDED USES

SPECTRUM TILE MATE CG 01 is used for grouting of tiles at Kitchens, Bathrooms, Shower stall, Swimming pools etc.

ADVANTAGES

- Water Resistance
- Chemical Resistance
- Excellent adhesion
- No need of wet curing
- Non-Shrink
- Best working time
- Non-Yellowing

APPLICATION METHOD


SPECTRUM TILE MATE CG 01 should be applied within the tile joints using a rubber spatula. Grout should be well compacted in to the joints. Remove surplus material by using a dry cloth and level the profile by using rounded tool.

SPECIAL NOTES

Grouting should commence only after the tile adhesive has dried completely. Joint must be clean, dry and free from dust or any loose material like tile adhesive. Use the wet grout within the pot life. When the grout is dry, polish tiles with clean, dry, soft cloth.

□ SPECTRUM TILE MATE CG 01

CEMENTITIOUS TILE GROUT



MIXING

Mix a full bag of SPECTRUM TILE MATE CG 01 with 2.9-3.5 Ltr of clean potable water. Mix with slow speed drill until to a homogeneous, lumps free paste is obtained. Allow to stand for ten minutes prior to use.

PACKING

It is available in 1 Kg & 10 Kg plastic bags.

COLOUR

It is available in 20 standard shades.

YIELD

Varies with tile dimension and grout width. Please refer to our grout calculation chart.

CLEANING

Water is all that needed to remove uncured grout. Cured material must be removed by mechanical means.

HEALTH AND SAFETY

Non hazardous. But we recommend to avoid inhalation of dust and contact with eyes. If ingested seek medical advice immediately.

TECHNICAL SERVICE

CHOKSEY CHEMICALS technical service department is pleased to offer full Technical support on specific application.

DISCLAIMER

The data is provided in the belief that is accurate within generally accepted standards and is provided for the information of qualified personnel. There is no guarantee is assumed on the performance of work completion executed with use of our product. The users therefore should make their own determination in using the product of the data contained herein for any application.