


# □ SPECTRUM TILE MATE EP

## High Performance Epoxy Tile Grout



### DESCRIPTION

SPECTRUM TILE MATE EP Two component Epoxy tile grout for CERAMICS TILES, VITRIFIED TILES , GLASS MOSAICS & STONES with high resistance to chemical attack. Imparts high harness, abrasion resistance & anti stain properties. Suitable for both floors and walls upto tile width 2 mm to 12 mm.

### RECOMMENDED USES

SPECTRUM TILE MATE EP is used for grouting of tiles at Kitchens, Bathrooms, Shower stall, Food Processing Units, Hospitals etc.

### ADVANTAGES

- High Strength
- Chemical Resistance
- Excellent adhesion
- Stain & bacterial Resistance
- Non-Shrink
- Best working time
- Non-Yellowing

### APPLICATION METHOD


SPECTRUM TILE MATE EP should be applied within the tile joints using a rubber spatula. Grout should be well compacted in to the joints. Remove surplus material by using a dry cloth and level the profile by using rounded tool.

### SPECIAL NOTES

Grouting should commence only after the tile adhesive has dried completely. Joint must be clean, dry and free from dust or any loose material like tile adhesive. Use the wet grout within the pot life. When the grout is in semi dry condition, polish tiles with sponge.

# **□ SPECTRUM TILE MATE EP**

## **High Performance Epoxy Tile Grout**



### **MIXING**

Mix Part A with Part B in the ratio of 2:1 by wt. Mix with slow speed drill until to a homogeneous paste is obtained.

### **PACKING**

It is available in 1 Kg & 5 Kg Kit boxes.

### **COLOUR**

It is available in variety of colours.

### **YIELD**

A full set of 1 Kg will gives a yield of 6.5 Ltr.

### **CLEANING**

Water/ grout cleaner is all that needed to remove uncured grout. Cured material must be removed by mechanical means.

### **HEALTH AND SAFETY**

All the ways we recommend to avoid inhalation of vapors for a prolonged time and contact with eyes and skin. If ingested seek medical advice immediately.

### **TECHNICAL SERVICE**

CHOKSEY CHEMICALS technical service department is pleased to offer full Technical support on specific application.