

FUTURA SEALER COAT

PRIMER COATING FOR FUTURA 5 & WALLNUT

DESCRIPTION

FUTURA SEALER is especially clear coating which acts as primer coat for Futura-5 and Wall nut or for any Elastomeric acrylic coating.

FEATURES / ADVANTAGES

- Fills the surface hairline cracks.
- Easily applicable by brush.
- It remains unaffected by UV rays.
- Enhances bonding with substrate and the topcoat.
- It can also used alone as a waterproof coating when applied two or three coats but always better to apply Futura 5 on it.

TYPICAL APPLICATIONS

To be applied over concrete surfaces.

TYPICAL CHARACTERISTICS

- Nature : single component, liquid
- Color : Turbid white becomes clear after drying.
- Specific gravity at 30°C : 1.00 ± 0.02
- Viscosity on ford cup B4 : 15 – 20 sec
- Inter-coat interval : 1 – 2 Hrs.
- Coverage : 80-100 sq.ft./coat/ltr.

DIRECTIONS FOR USE

Clean the surface with brush and ensure no loose particle remains on substrate. On a clean and dry substrate apply it with the help of brush. Allow it to dry for 1-2 Hrs then apply second coat and after 24Hrs apply Futura-5 coat.

CLEANING OF TOOLS AND EQUIPMENT

Tools and equipment can be easily cleaned with water. If it dries, it should be scrapped off.

STORAGE AND SHELF LIFE

In order to preserve all the properties, store the material in the original unopened containers in cool and dry place. Shelf life is Two years.

PACKING

4 liters, 20 liters